

Strebenprofil 20x20 3N, Nut 6, Rastermaß 20 mm, Länge 3000 mm, Aluminium eloxiert - Bosch Rexroth 3842517180

Item no. BRR-3842517180

Manufacturer Bosch Rexroth

Strut profile 20x20 of type 3N in anodized aluminum with three open type 6 slots and a 20 mm modular grid. Supplied in a 3000 mm standard length as a load-bearing base element for frames, machine bases and fixtures. Natural finish.

TECHNICAL DATA

Country of Manufacture Sweden

Hinweis

Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.

Length 3000 mm

Weight 35 kg

Zolltarifnummer 76042100



31370

DESCRIPTION

The Bosch Rexroth strut profile 20x20 of type 3N is a load-bearing base element of the aluminum profile system for frames, machine bases, safety enclosures and fixtures. The profile has three open slots of slot size 6 and a 20 mm modular grid, and is supplied in a 3000 mm standard length.

- Anodized surface in natural color, corrosion resistant
- Three open slots for flexible connection of connectors and accessories
- Compact 20x20 cross-section for lightweight structures
- Recommended accessory: cover cap 20x20, signal gray or black

TECHNICAL DATA

Cross-section	20x20 3N
Profile type	3N
Dimensions	20x20 mm
Length [L]	3000 mm
Profile slot	6
Open slots	3
Modular dimension	20 mm
Material	Aluminum, anodized

Color	natural
Profile surface [A]	1.7 cm ²
Mass [m]	0.5 kg/m
Area moment of inertia in x-direction [Ix]	0.7 cm ⁴
Area moment of inertia in y-direction [Iy]	0.8 cm ⁴
Moment of resistance in x-direction [Wx]	0.7 cm ³
Moment of resistance in y-direction [Wy]	0.7 cm ³
Torsional moment of inertia [It]	0.19 cm ⁴
Moment of torsion resistance [Wt]	0.34 cm ³
Condition on delivery	Packaging unit in standard length
Packaging unit	1
Delivery unit	20
Weight (delivery unit)	35 kg