

Anschlussstück G3/8" für Druckluft, Aluminiumdruckguss, Nut 10 - Bosch Rexroth 3842523092

Item no. BRR-3842523092

Manufacturer Bosch Rexroth

Connection piece for compressed-air intake or discharge at any point on the profile. The G3/8" port fits the central profile hole and suits light and standard profiles. The diecast aluminum flanged plate is rated for pressures up to 8 bar.

TECHNICAL DATA

Country of Manufacture **Germany**

Weight **0.094 kg**

Zolltarifnummer **83024900**



STANDARDS & COMPLIANCE

ISO4762

DESCRIPTION

This connection piece feeds compressed air into, or draws it from, any point on the aluminum profile. It is intended for design and assembly engineers who want to route compressed air directly within the profile system.

- G3/8" port located in the central profile hole
- suitable for light and standard profiles
- profile finishing: blind hole DI9.8 and blind hole ø21 mm (drilling jig 3842528574)
- rated for a maximum pressure of 8 bar

TECHNICAL DATA

Connection G3/8"

Max. pressure (pmax) 8 bar

Profile slot 10

Flanged plate material Diecast aluminum

Seal NBR

boxic24.com

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@boxic24.com

boxic24.com

Page 1/2

Fastening material	2x cylinder head screw ISO4762-M6x16, 2x T-nut slot 10 M6
Profile finishing	blind hole DI9.8; blind hole ø21 mm
Scope of delivery	incl. fastening material, seals
Required accessories	seals
Packaging unit	1
Weight	0.094 kg