

# Vereinzeler VE 2/D-200, gedämpft, für Transfersystem TS 2plus - Bosch Rexroth 3842524895

**Item no.** BRR-3842524895 **Manufacturer** Bosch Rexroth

**Manufacturer no.** 3842524895

Damped stop gate VE 2/D-200 for controlled stopping and separation of workpiece pallets on the TS 2plus transfer system. The hard-anodized aluminum housing and hardened steel stop cam provide high wear resistance. Pneumatically actuated and delivered fully assembled with mounting material for ST 2/... conveyor sections.

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
Country of Manufacture	<b>Germany</b>
ESD-Ausführung	<b>TEC</b>
Weight	<b>0.1 kg</b>
Zolltarifnummer	<b>84313900</b>



## STANDARDS & COMPLIANCE

ESD safe

## DESCRIPTION

The damped stop gate VE 2/D-200 stops workpiece pallets in a controlled manner on the TS 2plus transfer system and separates them for downstream processing or handling stations. The integrated damping reduces impact and protects both pallets and workpieces.

- Hard-anodized aluminum housing and hardened steel stop cam for high wear resistance
- Pneumatically actuated, delivered fully assembled with fastening material for ST 2/... conveyor sections
- High-temperature version available on request

## Technical data

Attribute	Value
Housing	Aluminum, hard anodized
Stop cam	Steel, hardened
Required compressed air connection pmin	4 bar
Required compressed air connection pmax	6 bar
Pneumatic straight connection Ø	6 mm
Operating temperature T max	0 ... +60 °C
Min. workpiece pallet weight	5 kg
Workpiece pallet total weight mG	200 kg
Nominal speed	6, 9, 12, 15, 18, 24, 30 m/min
Permissible total weight per nominal speed	200, 140, 100, 100, 100, 55, 35 kg
Scope of delivery	incl. all fastening material to mount on ST 2/... conveyor section
Delivery condition	fully assembled
Recommended accessories	VE 2/RS Return Stop
Weight	1.931 kg