

Wüfelverbinder 40/3, ESD, Profil 40x40, Nut 10, Aluminiumdruckguss - Bosch Rexroth 3842529011

Item no. BRR-3842529011

Manufacturer Bosch Rexroth

The cubic connector 40/3 joins three 40x40 aluminum profiles at right angles in a single node. It is electrostatically conductive (ESD) and carries a bending moment of up to 70 Nm per joint. It is used to build frames and machine structures from the strut profile system with slot 10.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	Portugal
Weight	0.084 kg
Zolltarifnummer	83024900



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Bosch Rexroth cubic connector 40/3 joins three 40x40 aluminum profiles at right angles in one common node. It is intended for designers and assemblers building stable frames, machine structures and fixtures from the strut profile system with slot 10.

- Three outlets for a compact corner joint in a single point
- Electrostatically conductive (ESD) for use in electrostatic discharge protected areas
- Rated up to 70 Nm bending moment per joint (3P)
- Rugged diecast aluminum

TECHNICAL DATA

Profile slot	10
Dimensions	40x40
ESD	yes
Number of outlets	3
Bending moment 3P	70 Nm

boxic24.com

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@boxic24.com

boxic24.com

Page 1/2

Material	Diecast aluminum
Packaging unit	20 pcs
Recommended accessories	Countersunk screw S12x30, cover cap D24 signal gray (PP), cover cap D24 black (PP)
Weight	0.084 kg