

Nutenstein 8 M6, einschwenkbar, ESD, Stahl verzinkt - Bosch Rexroth 3842529296

Item no. BRR-3842529296 **Manufacturer** Bosch Rexroth**Manufacturer no.** 3842529296

The T-slot nut 8 with M6 thread fastens add-on components to aluminum profiles with slot 8. Its swivel-in design allows insertion into already assembled profiles. ESD-capable, made of galvanized steel with a stainless spring.

TECHNICAL DATA

| | |
|----------------------|-------------------------|
| Article authenticity | Original product |
| Condition of article | New |
| ESD-Ausführung | ESD (antistatic) |
| Weight | 0.00529 kg |
| Zolltarifnummer | 73181692 |



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The T-slot nut 8 with M6 thread is used to fasten add-on components to aluminum profiles with slot 8. Its swivel-in design allows it to be inserted into the profile groove afterwards, without using the end of the profile. The preloaded spring holds the nut in position.

- Swivel-in design for retrofitting in already assembled profiles
- ESD-capable for applications with electrostatic requirements
- Groove retention up to 2200 N
- Galvanized steel with a stainless spring steel spring

Technical data

| | |
|--------------|-----|
| Profile slot | 8 |
| Thread size | M6 |
| Swivel-in | yes |

| | |
|-----------------------|---|
| ESD | yes |
| Length l | 16 mm |
| Dimension h | 4.8 mm |
| Dimension h1 | 1 mm |
| Groove retention Fmax | 2200 N |
| Material | Steel, galvanized |
| Material information | Steel galvanized, spring: spring steel, stainless |
| Packaging unit | 100 pcs |
| Weight | 0.00529 kg |