

Vereinzeler VE 2/M, pneumatisch, Staulast bis 200 kg - Bosch Rexroth 3842531610

Item no. BRR-3842531610 **Manufacturer** Bosch Rexroth

Manufacturer no. 3842531610

The pneumatic VE 2/M tilting stop gate halts accumulating workpiece pallets up to 200 kg at a defined stop surface. It opens without abrasion and runs especially quietly. It mounts directly within the tracks on the conveyor section of the TS 2plus transfer system.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Country of Manufacture	Italy
ESD-Ausführung	TEC
Weight	0.0099 kg
Zolltarifnummer	84313900



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The VE 2/M stop gate is a pneumatic tilting stop gate for the Bosch Rexroth TS 2plus transfer system. It stops one or more accumulating workpiece pallets at the defined stop surface and is mounted within the tracks directly on the conveyor section.

- Tilting function opens without causing abrasion on the workpiece pallet stop surface
- Low-noise design for especially quiet opening and closing
- In the depressurized state a spring moves the gate into the blocking position
- Combinable with the WT 2, WT 2/E and WT 2/F workpiece pallets

Reversible operation is not permitted. High-temperature stop gate available on request. Supplied including all fastening material to mount on the ST 2/... conveyor section and pneumatic elements.

Technical data

Article number	3842531610
Type	Tilting stop gate, pneumatic
Max. workpiece pallet total weight	200 kg
Operating temperature	0 ... +60 °C
A-rated emission sound pressure level	< 60 dB(A)
Required compressed air connection	4 ... 6 bar
Pneumatic straight connection	Ø 4 mm
Housing	PA 6
Safety catch	Brass
Stop cam	PA 66
Weight	0.35 kg
Delivery condition	Fully assembled

Permissible accumulation load

Total weight mG (kg) Nominal speed vN (m/min)

200	6
140	9
100	12
70	15
50	18