

Laufrolle D50 ESD mit Feststeller, M8, Nut 8/10 - Bosch Rexroth 3842535670

Item no. BRR-3842535670

Manufacturer Bosch Rexroth

Electrically conductive (ESD) idle roller with lock, made of polyamide, for building mobile fixtures and trolleys in aluminium profile systems. It mounts with M8 and the supplied T-slot nut in profile slot 8 or 10 and carries up to 400 N.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Colour	Black
Country of Manufacture	Germany
Weight	0.137 kg
Zolltarifnummer	83022000



STANDARDS & COMPLIANCE

ESD safe DIN EN 12528 DIN 9021 8.4

DESCRIPTION

This electrically conductive (ESD) idle roller from Bosch Rexroth is used to build mobile fixtures, trolleys and workstations in aluminium profile systems. It suits areas requiring protection against electrostatic discharge and can be immobilised with the integrated lock.

- Conductive ESD version to DIN EN 12528
- Lock to block the roller in place
- Mounts in profile slot 8 or 10 with the supplied T-slot nut
- Load capacity up to 400 N

TECHNICAL DATA

Profile slot	8, 10
ESD	yes
Conduction resistance	$\leq 10^6 \Omega$ (DIN EN 12528)
Color	Black
Total height	63 mm

Force F	400 N
Material	PA (housing, wheel, lock)
Fastening material	1x T-slot nut slot 8 M8, 1x T-slot nut slot 10 M8, 1x washer DIN 9021 8.4 (steel, galvanized)
Packaging unit	4
Weight	0.137 kg