

Strebenprofil 40x120x120L, ESD, Aluminium eloxiert, Nut 10 - Bosch Rexroth 3842538287

Item no. BRR-3842538287 **Manufacturer** Bosch Rexroth

Manufacturer no. 3842538287

Angled strut profile 40x120x120L made of anodized aluminum with profile slot 10 for the modular construction of frames and machine bases. ESD-capable and therefore suitable for electrostatically protected areas. Supplied as a packaging unit of 4 profiles, 6070 mm each.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Country of Manufacture	Sweden
Hinweis	Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.
Lenght	6070 mm
Weight	175 kg
Zolltarifnummer	76042100



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The angled strut profile 40x120x120L from Bosch Rexroth is a load-bearing basic element made of anodized aluminum for building frames, machine bases and support structures. With profile slot 10 and a 40 mm modular dimension, it integrates flexibly into the profile construction system.

- Angled L-geometry 40x120x120 for rigid, bending-resistant structures
- ESD-capable for use in electrostatically protected areas

- Anodized natural surface, corrosion-resistant and low-maintenance
- Supplied as a packaging unit of 4 profiles, 6070 mm each

Technical data

Cross-section	40x120x120L
Dimensions	40x120x120
Profile type	angled
Modular dimension	40 mm
Profile slot	10
Open slots	12
ESD	yes
Color	Natural
Material	Aluminum, anodized
Length [L]	6070 mm
Delivery unit	4 profiles
Condition on delivery	Packaging unit in standard length
Profile surface [A]	24.6 cm ²
Area moment of inertia [Ix]	318 cm ⁴
Area moment of inertia [Iy]	318 cm ⁴
Moment of resistance [Wx]	42.2 cm ³
Moment of resistance [Wy]	42.2 cm ³
Torsional moment of inertia [It]	37.1 cm ⁴
Moment of torsion resistance [Wt]	19 cm ³
Mass [m]	6.7 kg/m
Weight	175 kg
Recommended accessories	Cover cap 40x40 and 40x80, signal gray or black