

Lenkrolle D80, thermoplastischer Gummi, ESD, Nut 10 - Bosch Rexroth 3842541230

Item no. BRR-3842541230

Manufacturer Bosch Rexroth

Swivel caster with an 80 mm thermoplastic rubber wheel for static-dissipative (ESD) applications. Rated for up to 900 N and mounted directly to aluminium profile via slot 10. Adds floor-friendly mobility to assembly fixtures and workstation systems.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Weight	0.64 kg
Zolltarifnummer	83022000



STANDARDS & COMPLIANCE

ESD safe ISO 4762

DESCRIPTION

The Bosch Rexroth D80 swivel caster adds mobility to assembly fixtures, workbenches and transport trolleys built from the aluminium profile system. The thermoplastic rubber wheel protects the floor and, with a conduction resistance of $\leq 10^6 \Omega$, suits electrostatically protected (ESD) work areas.

- Floor-friendly thermoplastic rubber wheel
- Static-dissipative (ESD) for EPA zones
- Rated for loads up to 900 N
- Direct mounting to the profile via slot 10

TECHNICAL DATA

Diameter D	80 mm
Force F	900 N
Total height	108 mm
Material	Thermoplastic rubber
Conduction resistance (RA)	$\leq 10^6 \Omega$

boxic24.com

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680

shop@boxic24.com

boxic24.com

Page 1/2

ESD	yes
Profile slot	10
Fastening material	1x square screw M12x30, 1x hexagon nut DIN985 M12
Required accessories	Screw M12x40 (ISO 4762) for fastening to the profile core, tightening torque 35 Nm; bearing ring if a cover cap with hole is used
Packaging unit	1
Weight	0.64 kg