

Lenkrolle D125 F, thermoplastischer Gummi, ESD, Nut 10 - Bosch Rexroth 3842541232

Item no. BRR-3842541232

Manufacturer Bosch Rexroth

Electrically conductive swivel caster with a thermoplastic rubber tread for mobile equipment built in the slot 10 profile system. Its defined conduction resistance of $\leq 10^6 \Omega$ protects ESD-sensitive components during transport. Rated for loads up to 1100 N per caster.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Weight	0.839 kg
Zolltarifnummer	83022000



STANDARDS & COMPLIANCE

ESD safe ISO 4762

DESCRIPTION

The Swivel Caster D125 F ESD from Bosch Rexroth is an electrically conductive floor caster for mobile assembly and transport equipment in the aluminium profile system with slot 10. The thermoplastic rubber tread runs quietly and protects the floor, while the defined conduction resistance safely dissipates electrostatic charges.

- Conduction resistance $\leq 10^6 \Omega$ to protect ESD-sensitive components
- Floor-protecting tread made of thermoplastic rubber
- Rated for loads up to 1100 N per caster
- Direct fastening into the profile core with slot 10

TECHNICAL DATA

Profile slot	10
ESD	yes
Diameter D	125 mm
Total height	158 mm

boxic24.com

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@boxic24.com

boxic24.com

Page 1/2

Force F	1100 N
Material	Thermoplastic rubber
Conduction resistance [RA]	$\leq 10^6 \Omega$
Fastening material	1x square screw M12x30, 1x hexagon nut DIN985 M12
Required accessories	Screw M12x40 (ISO 4762) for fastening to the profile core (tightening torque 35 Nm), bearing ring if a cover cap with hole is used
Packaging unit	1
Weight	0.839 kg