

Bockrolle D125 ESD, bodenschonend, Nut 10 - Bosch Rexroth 3842541244

Item no. BRR-3842541244

Manufacturer Bosch Rexroth

Floor-protecting trestle roller with a thermoplastic rubber tread for ESD-compliant use. The dissipative design ($\leq 10^6 \Omega$) protects electrostatically sensitive components. Mounts to profiles with slot 10 using the supplied M12x22 square screw.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Weight	0.63 kg
Zolltarifnummer	83022000



STANDARDS & COMPLIANCE

ESD safe ISO 4762

DESCRIPTION

The D125 ESD trestle roller from Bosch Rexroth is a floor-protecting roller for assembly trolleys and frames in ESD areas. Its thermoplastic rubber tread protects sensitive floors while maintaining a dissipative contact to the ground.

- Floor-protecting thermoplastic rubber tread
- Dissipative ($\leq 10^6 \Omega$) for ESD-compliant use
- Load capacity up to 1100 N per roller
- Simple mounting on profiles with slot 10

TECHNICAL DATA

Profile slot	10
Diameter D	125 mm
Total height (h)	158 mm
Force F	1100 N
Material	Thermoplastic rubber

ESD	yes
Conduction resistance (RA)	$\leq 10^6 \Omega$
Fastening material	1x square screw M12x22, 1x hexagon nut DIN985 M12
Required accessories	Screw M12x40 (ISO 4762) for fastening to the profile core (tightening torque 35 Nm), bearing ring if a cover cap with hole is used
Packaging unit	1
Weight	0.63 kg