

Gelenk 40x40, ESD, Aluminiumdruckguss, Nut 10 - Bosch Rexroth 3842543402

Item no. BRR-3842543402

Manufacturer Bosch Rexroth

Pivoting joint for the angle-adjustable connection of 40x40 profiles with slot 10. Made of diecast aluminum, ESD-capable, with a 180° swivel range. Fastening material is included in delivery.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**

Country of Manufacture **Turkey**

Weight **0.31 kg**

Zolltarifnummer **83024900**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Bosch Rexroth 40x40 joint connects two profiles of the 40x40 series at an adjustable angle and forms a pivoting support point for machine and workstation construction. The ESD version dissipates electrostatic charges and suits workplaces that handle sensitive electronic components. The required fastening material is included in delivery.

- 180° swivel range for flexible angle adjustment
- ESD-capable through electrically conductive design
- Load capacity F1 15000 N and F2 1000 N
- Fastening material included (FS)

TECHNICAL DATA

Profile slot	10
Modular dimension	40 mm
Dimensions	40x40
ESD	yes

Swivel range	180°
Force F1	15000 N
Force F2	1000 N
Material	Diecast aluminum
Material information	Joint: Diecast aluminum; fastening material: steel, galvanized
Fastening material	2x flange head screw M8x16, 2x T-nut groove 10 M8, 2x screw S12x30
Scope of delivery	incl. fastening material (FS)
Recommended accessory	Clamping lever 3842516847
Packaging unit	1
Weight	0.31 kg