

Lenkrolle mit Feststeller D125, Vollgummi, ESD, F800, Nut 10 - Bosch Rexroth 3842547838

Item no. BRR-3842547838

Manufacturer Bosch Rexroth

Swivel castor with lock for mounting frames and fixtures built from aluminum profile in slot 10. The solid rubber tread runs smoothly and keeps its shape even after long idle periods. The conductive ESD design suits electrostatically protected areas.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Weight	0.839 kg
Zolltarifnummer	83022000



STANDARDS & COMPLIANCE

ESD safe DIN EN 61340-5-1 ISO 4762

DESCRIPTION

Swivel castor with lock for making frames and fixtures from the aluminum profile system mobile. The castor is fastened in profile slot 10 or in the profile core (accessories required) and lets the assembly be moved easily.

- Solid rubber running surface with good deformation elasticity, no permanent flattening after long idle periods or travel over edges
- Excellent running properties
- Lock prevents the wheel from rolling and turning
- Conductive version in accordance with DIN EN 61340-5-1 for ESD-protected areas

TECHNICAL DATA

Feature	Value
Type	Swivel castor with lock
Material	Solid rubber
Load capacity F	800 N

Feature	Value
Diameter D	125 mm
Height h	158 mm
Profile slot	10
ESD	yes
Conduction resistance RA	$\leq 10^6 \Omega$
Fastening material	1x square screw M12x30, 1x hexagon nut DIN985 M12
Required accessories	Screw M12x40 (ISO 4762) for fastening to the profile core, 35 Nm; bearing ring if cover cap with hole is used
Packaging unit	1
Weight	0.839 kg