

Dämpfer DA 2/100-E zum Ausschleusen der Werkstückträger, TS 2plus - Bosch Rexroth 3842548585

Item no. BRR-3842548585 **Manufacturer** Bosch Rexroth

Manufacturer no. 3842548585

Pneumatic damper DA 2/100-E for the controlled outfeeding of WT 2 workpiece pallets in the TS 2plus transfer system. Hard-anodized aluminum housing with a hardened steel stop. Mounts on an HQ 2/U-H or HQ 2/C-H stop gate.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
ESD-Ausführung	TEC
Weight	2.1 kg
Zolltarifnummer	84313900



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Bosch Rexroth DA 2/100-E damper is used for the controlled outfeeding of WT 2, WT 2/F, WT 2/H or WT 2/F-H workpiece pallets in the TS 2plus transfer system. It mounts on an HQ 2/U-H or HQ 2/C-H stop gate and gently decelerates the pallet during transfer.

- Suitable for workpiece pallet total weights up to 100 kg, depending on nominal speed
- Rugged housing in hard-anodized aluminum with a hardened steel stop
- Pneumatic connection via 6 mm straight push-in fitting
- High-temperature damper available on request

Technical data

Mass [m]	5 kg
Workpiece pallet total weight [mG]	100 kg
Nominal speed	6, 9, 12, 15, 18 m/min

Max. total weight per speed	100 / 100 / 100 / 95 / 55 kg
Operating temperature	0 ... +60 °C
Pneumatic straight connection Ø	6 mm
Housing	Aluminum, hard anodized
Stop	Steel, hardened
Scope of delivery	incl. fastening material
Delivery information	not assembled
Weight	2.1 kg