

# Kurvenrad 65+ AL 30° ESD für VarioFlow plus Kettenfördersystem - Bosch Rexroth 3842553029

**Item no.** BRR-3842553029 **Manufacturer** Bosch Rexroth

**Manufacturer no.** 3842553029

Pre-assembled ESD cam wheel with a 30° deflection angle for the VarioFlow plus chain conveyor system, size 65 mm. The diecast aluminum housing and PA ESD chain wheel (black) provide reliable electrostatic discharge along the conveyor line. Supplied fully assembled, including fastening material for direct mounting to the AL section profile.

## TECHNICAL DATA

|                        |                         |
|------------------------|-------------------------|
| Article authenticity   | <b>Original product</b> |
| Condition of article   | <b>New</b>              |
| Country of Manufacture | <b>Germany</b>          |
| ESD-Ausführung         | <b>ESD (antistatic)</b> |
| Weight                 | <b>3.46 kg</b>          |
| Zolltarifnummer        | <b>84313900</b>         |



## STANDARDS & COMPLIANCE

ESD safe

## DESCRIPTION

The cam wheel 65+ AL ESD deflects conveyor chains in the VarioFlow plus system by 30° and is designed specifically for ESD-sensitive production environments. It is delivered fully assembled and mounts directly to the AL section profile - no additional machining required.

- ESD-compliant: PA ESD chain wheel (black) safely dissipates electrostatic charges
- Diecast aluminum housing - rigid, lightweight and corrosion-resistant
- Ball bearing in non-rusting steel 1.4301/FDA - suitable for hygiene-critical environments
- Delivered with all fastening material for AL section profile - ready to install
- Effective sliding rail length 2 x 0.34 m, actual chain length 2 x 0.28 m

## Technical data

| Attribute                     | Value                        |
|-------------------------------|------------------------------|
| Size [b]                      | 65 mm                        |
| Deflection angle [ $\alpha$ ] | 30°                          |
| Dimension [A]                 | 185.5 mm                     |
| ESD                           | yes                          |
| Housing                       | Diecast aluminum             |
| Chain wheel                   | PA ESD, black                |
| Ball bearing                  | Non-rusting steel 1.4301/FDA |
| Effective sliding rail length | 2 x 0.34 m                   |
| Actual chain length           | 2 x 0.28 m                   |
| Delivery condition            | Fully assembled              |
| Weight                        | 3.46 kg                      |