

Gelenkfuß D44 M16x200, ESD, verzinkt, 20 kN - Bosch Rexroth 3842554149

Item no. BRR-3842554149

Manufacturer Bosch Rexroth

Galvanized steel leveling foot with M16x200 thread and 44 mm base plate for slot-10 aluminum profile systems. Rated to 20,000 N axial force, ESD-approved, with 135 mm adjustment range. A bearing ring is recommended when using cover caps with a hole.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	China
Lenght	200 mm
Weight	0.347 kg
Zolltarifnummer	73181595



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Leveling Foot D44 M16x200 levels and supports aluminum profile assemblies built on slot-10 sections, handling up to 20,000 N axial force. The galvanized M16 steel spindle runs 200 mm long and provides 135 mm of height adjustment; the 44 mm articulating base plate compensates for uneven floors. ESD suitability is confirmed by the manufacturer.

- High load capacity: 20,000 N axial force for heavy machine frames and workstations
- Wide adjustment range: 135 mm to accommodate floor irregularities and varying frame heights
- ESD-safe: suitable for electrostatic-protected work areas (EPA)
- Galvanized steel: corrosion-resistant for industrial and production environments
- Designed for Bosch Rexroth slot-10 aluminum profile system

TECHNICAL DATA

Attribute	Value
Thread size	M16
Length L	200 mm
Diameter D	44 mm

boxic24.com

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@boxic24.com

boxic24.com

Page 1/2

Attribute	Value
Adjustment range V	135 mm
Force F	20,000 N
Profile slot	10
Material	Steel, galvanized
ESD	Yes
Weight	0.347 kg
Packaging unit	20 pieces
Recommended accessories	Bearing ring for use with cover caps with a hole