

Strebenprofil 15x22,5, Aluminium eloxiert, variable Länge 50-3000 mm - Bosch Rexroth 3842992473

Item no. BRR-3842992473

Manufacturer Bosch Rexroth

Compact anodized aluminum strut profile with a 15x22.5 mm cross-section for lightweight support structures and frames in the Bosch Rexroth 45 mm modular assembly system. Supplied as a cut-to-length piece between 50 mm and 3000 mm, natural finish, with one open 10 mm profile slot for standard Rexroth connectors and T-nuts.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
Hinweis	Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.
Weight	0.1 kg
Zolltarifnummer	76042100



31447

DESCRIPTION

The Strut Profile 15x22.5 is an anodized aluminum profile with a compact rectangular cross-section, designed for lightweight support and bracing applications within the Bosch Rexroth Assembly Technology system. Supplied cut-to-length in any dimension from 50 mm to 3000 mm, it integrates directly into the 45 mm modular grid shared across the Rexroth profile range.

- Cut-to-length delivery from 50 mm to 3000 mm - ordered to exact project requirements
- Anodized aluminum surface (natural) - corrosion-resistant with lasting dimensional stability
- One open 10 mm profile slot accepts standard connectors and T-slot nuts for the 45 mm system
- Low mass (0.3 kg/m) simplifies handling and integration into larger assemblies

TECHNICAL DATA

Property	Value
Cross-section	15x22.5 mm
Profile type	Standard
Modular dimension	45 mm
Profile slot	10 mm
Open slots	1
Length min. (L min)	50 mm

boxic24.com

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680

shop@boxic24.com

boxic24.com

Page 1/2

Property	Value
Length max. (L max)	3000 mm
Condition on delivery	Variable length (cut to length)
Material	Aluminum, anodized
Color	Natural
Area moment of inertia I _x	0.8 cm ⁴
Area moment of inertia I _y	0.3 cm ⁴
Moment of resistance W _x	0.9 cm ³
Moment of resistance W _y	0.6 cm ³
Profile surface A	1.3 cm ²
Mass	0.3 kg/m
Packaging unit	1
Recommended accessories	Cover cap 15x22.5 signal gray, Cover cap 15x22.5 black