

Rahmenprofil 22,5x30, Aluminium eloxiert, variable Länge 50-6070 mm - Bosch Rexroth 3842992493

Item no. BRR-3842992493

Manufacturer Bosch Rexroth

Extruded anodized aluminum frame profile with a 22.5x30 mm cross-section and slot 8 for the Bosch Rexroth manual assembly system. Supplied cut to size - lengths from 50 mm to 6070 mm available to order. Recommended accessories: bracket set M6, swivel fastening, and matching cover caps.

TECHNICAL DATA

Country of Manufacture **Germany**

Hinweis **Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.**

Weight **0.018 kg**

Zolltarifnummer **76042100**



20238

DESCRIPTION

The Frame Profile 22.5x30 in anodized aluminum is a core structural component for Bosch Rexroth manual production systems and workstation assemblies. It is sold at a cut-to-size price in variable lengths - minimum 50 mm, maximum 6070 mm - supplied as individual pieces. Slot 8 along the profile accepts the full range of system-compatible connectors, swivel fastenings, and labeling clips without additional machining.

- Cut-to-size lengths from 50 mm to 6070 mm, delivered as a single unit
- Slot 8 for direct, tool-compatible assembly with brackets, plates, and clips
- Anodized aluminum: corrosion-resistant, lightweight, and durable
- Profile surface area 3.2 cm², mass 0.9 kg/m - straightforward integration into frame structures

TECHNICAL DATA

Property	Value
Condition on delivery	Variable length
Length min. [L min]	50 mm
Length max. [L max]	6070 mm
Delivery unit	1 piece
Profile slot	8

boxic24.com

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@boxic24.com

boxic24.com

Page 1/2

Property	Value
Profile surface [A]	3.2 cm ²
Mass [m]	0.9 kg/m
Area moment of inertia X [Ix]	1.7 cm ⁴
Moment of resistance X [Wx]	1.5 cm ³
Area moment of inertia Y [Iy]	3.0 cm ⁴
Moment of resistance Y [Wy]	2.0 cm ³
Material	Aluminum, anodized
Recommended accessories	Bracket set M6, swivel fastening, lettering clip slot 8 mm, plate, cover cap 22.5x30 black, cover cap 22.5x30 signal gray