

# Klemmprofil 1S, Nut 8 mm, 50-3000 mm Zuschnittlänge - Bosch Rexroth 3842993017

**Item no.** BRR-3842993017 **Manufacturer** Bosch Rexroth

**Manufacturer no.** 3842993017

Single-sided clamping profile in anodized aluminum for securing panes, surface elements, or grilles in 8 mm slot strut profiles. Supplied cut-to-length between 50 mm and 3,000 mm, with a through-hole for the mounting screw already machined. Suitable for subsequent installation in closed frame constructions without disassembly.

## TECHNICAL DATA



Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
Country of Manufacture	<b>Germany</b>
ESD-Ausführung	<b>TEC</b>
Hinweis	<b>Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.</b>
Weight	<b>0.0099 kg</b>
Zolltarifnummer	<b>76109090</b>

## STANDARDS & COMPLIANCE

**ESD safe** **ISO 4762**

## DESCRIPTION

The Bosch Rexroth Clamping Profile 1S provides a secure, form-fit fixing of panes, surface elements and grilles in 8 mm slot strut profiles. The variable cut-to-length delivery and pre-machined through-hole allow installation even after a frame has been assembled, keeping retrofit work straightforward.

- Designed for 8 mm slot strut profiles

- Cut-to-length: 50 mm to 3,000 mm ordered per linear metre
- Single-sided clamping (1S) - accommodates surface elements of varying thickness
- Material: aluminum, anodized - lightweight and corrosion-resistant
- Through-hole for mounting screw pre-machined
- Suitable for subsequent installation in closed frame constructions

## Technical data

Property	Value
Type	Clamping profile 1S
Profile slot	8 mm
Length min.	50 mm
Length max.	3,000 mm
Condition on delivery	Cut-to-length (variable)
Delivery unit	1 piece
Profile finishing	Through-hole for mounting screw
Material	Aluminum, anodized
Required accessories	Cylinder head screw DIN EN ISO 4762 M4x20 (8 mm slot)
Article number	3842993017