

Antriebsstation AS 2/R-1200, Spurbreite 160-1200 mm, ESD - Bosch Rexroth 3842998040

Item no. BRR-3842998040**Manufacturer Bosch Rexroth**

Drive module for the TS 2plus transfer system with accumulating roller chain, supplied fully assembled. Track width adjustable from 160 to 1200 mm; section load in accumulation operation up to 1200 kg. ESD-compliant design for use in electrostatic protected areas.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
Weight	0.1 kg
Zolltarifnummer	84313900



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Drive Module AS 2/R-1200 powers the accumulating roller chain in the TS 2plus transfer system. It covers a wide track-width range and handles high accumulation loads, and is delivered fully assembled for fast installation.

- Track width continuously adjustable from 160 to 1200 mm - accommodates a broad range of workpiece carriers
- Section load in accumulation operation up to 1200 kg - reliable performance under high parts accumulation
- Preferred track-width values: 160, 240, 320, 400, 480, 640, 800, 1040 and 1200 mm
- Conveyor medium length IAS: 625 mm
- ESD-compliant - suitable for electrostatically protected production areas
- Supplied fully assembled - minimal on-site installation effort
- Recommended accessory: LU 2 Automatic Lubrication Unit

TECHNICAL DATA

Parameter	Value
Product family	TS 2plus transfer system, accumulating roller chain
Conveyor medium length IAS	625 mm
Track width min (b min)	160 mm
Track width max (b max)	1200 mm
Preferred track-width values	160, 240, 320, 400, 480, 640, 800, 1040, 1200 mm
Section load in accumulation operation	1200 kg
ESD-compliant	Yes
Delivery condition	Fully assembled
Recommended accessory	LU 2 Automatic Lubrication Unit