

# Antriebsstation AS 2/C-250 für Transfersystem TS 2plus, Spurbreite 160-1200 mm - Bosch Rexroth 3842998087

**Item no.** BRR-3842998087 **Manufacturer** Bosch Rexroth

**Manufacturer no.** 3842998087

Fully assembled drive module for the TS 2plus flat-top chain transfer system, rated for a section load of 250 kg in accumulation mode and ESD-safe for use in EPA environments (KA = A). Conveyor medium length is 475 mm; track width is freely selectable from 160 to 1200 mm, with custom widths available on request. Delivery includes all fastening material for mounting to the ST 2/... conveyor section and an adjacent return unit.

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
Country of Manufacture	<b>Germany</b>
ESD-Ausführung	<b>TEC</b>
Weight	<b>0.1 kg</b>
Zolltarifnummer	<b>84313900</b>



## STANDARDS & COMPLIANCE

**ESD safe**

## DESCRIPTION

The Drive Module AS 2/C-250 powers the flat-top chain in the TS 2plus transfer system and is rated for a section load of 250 kg in accumulation operation. It is supplied fully assembled and bolts directly to the ST 2/... conveyor section and any adjacent return unit - all required fastening material is included. The ESD-safe chain construction (KA = A) qualifies the module for use in Electrostatic Protected Areas (EPA). Nine preferred track widths between 160 and 1200 mm are available as standard; non-standard widths can be ordered individually.

- Section load up to 250 kg in accumulation mode

- ESD-safe chain, approved for EPA use (KA = A)
- Conveyor medium length 475 mm
- Track width 160 to 1200 mm, preferred values or custom
- Supplied fully assembled, including all fastening hardware
- Suitable for dry rooms (<1 %rF)

## Technical data

Parameter	Value
Section load in accumulation mode	250 kg
Conveyor medium length [IAS]	475 mm
Track width min [b min]	160 mm
Track width max [b max]	1200 mm
Preferred track width values	160, 240, 320, 400, 480, 640, 800, 1040, 1200 mm
ESD suitability	Yes (KA = A, EPA-approved)
Dry room	<1 %rF
Delivery condition	Fully assembled
Scope of delivery	Incl. fastening material for ST 2/... and return unit
Recommended accessories	Connection Kits, LU 2 Automatic Lubrication Unit