

Antriebsstation AS 2/R-2200 Vplus, Streckenbelastung 2200 kg, ESD-geeignet - Bosch Rexroth 3842998234

Item no. BRR-3842998234 **Manufacturer** Bosch Rexroth

Manufacturer no. 3842998234

Drive module for the TS 2plus transfer system with Vplus accumulation roller chain, rated for section loads up to 2200 kg in accumulation mode. The conveyor medium measures 625 mm in length and the unit supports track widths from 400 to 1200 mm. Supplied fully assembled and ESD-suitable.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Country of Manufacture	Germany
ESD-Ausführung	TEC
Weight	0.1 kg
Zolltarifnummer	84313900



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Drive Module AS 2/R-2200 Vplus powers the Vplus accumulation roller chain in the TS 2plus transfer system and handles section loads up to 2200 kg in accumulation operation. Supplied fully assembled, it is ready for installation without pre-assembly work and meets ESD requirements for electrostatically sensitive production environments.

- Section load up to 2200 kg in accumulation mode - suited to heavy pallet carriers and linked assembly lines
- ESD-suitable - safe operation in electrostatically sensitive areas
- Track width 400 to 1200 mm - compatible with all preferred values 400, 480, 640, 800, 1040 and 1200 mm
- Conveyor medium length 625 mm - matches standard section units of the TS 2plus

- Supplied fully assembled - no pre-assembly required, installation-ready on delivery

Technical data

Attribute	Value
Type	AS 2/R-2200 Vplus
System	Transfer system TS 2plus, Vplus accumulation roller chain
Section load in accumulation operation	2200 kg
Conveyor medium length [IAS]	625 mm
Track width min [b min]	400 mm
Track width max [b max]	1200 mm
Preferred track width values	400, 480, 640, 800, 1040, 1200 mm
ESD-suitable	yes
Delivery condition	Fully assembled
Recommended accessories	LU 2 Automatic Lubrication Unit