

# Werkstückträger WT 2/H 12,7 mm für Transfersystem TS 2plus, ESD-geeignet - Bosch Rexroth 3842998751

**Item no.** BRR-3842998751 **Manufacturer** Bosch Rexroth

**Manufacturer no.** 3842998751

Aluminum workpiece pallet for the TS 2plus transfer system with a 12.7 mm carrying plate, covering 17 standard sizes from 400 x 400 mm to 1200 x 1200 mm. PE wear pads and integrated stop dampers ensure quiet, low-wear operation. Available fully assembled (MT 1) or as a self-assembly kit (MT 0), ESD-suitable.

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
Country of Manufacture	<b>Germany</b>
ESD-Ausführung	<b>TEC</b>
Weight	<b>0.0099 kg</b>
Zolltarifnummer	<b>84662020</b>



## STANDARDS & COMPLIANCE

ESD safe

## DESCRIPTION

The WT 2/H 12.7 workpiece pallet carries and transports parts within the TS 2plus transfer system, supporting combined workpiece weights of up to 240 kg. The universal aluminum carrying plate - 12.7 mm thick - is available in 17 standard sizes (bWT x IWT = 400 x 400 mm to 1200 x 1200 mm); special dimensions are available on request. PE wear pads on the corner modules and sliders keep running noise and wear to a minimum, while integrated stop dampers absorb the impact when pallets accumulate behind one another. Certified for use in electrostatic protected areas (EPA).

- 12.7 mm carrying plate thickness - fits the full TS 2plus product range
- PE wear pads on corner modules and sliders for quiet, low-wear operation
- Integrated stop dampers for smooth pallet accumulation without impact
- 17 standard sizes, square and rectangular combinations from 400 mm to 1200 mm

- Supplied fully assembled (MT = 1) or as a kit for self-assembly (MT = 0)
- ESD-suitable for use in EPA environments

## Technical data

Parameter	Value
Carrying plate thickness dPL	12.7 mm
Carrying plate material	Aluminum
Corner modules / sliders	PE (polyethylene)
Max. workpiece pallet total weight mG	240 kg
Workpiece pallet width bWT	400 / 480 / 640 / 800 / 1040 / 1200 mm
Workpiece pallet length IWT	400 / 480 / 640 / 800 / 1040 / 1200 mm
Number of standard sizes	17
ESD-suitable	Yes
Delivery state	Assembled (MT = 1) or kit, not assembled (MT = 0)
Scope of delivery	Carrying plate, corner modules, wear pads, damping elements
Recommended accessory	2x positioning bushing kit WT 2/H LE 2 (required when using PE 2/H positioning unit)
Weight (catalog entry)	0.0099 kg (varies by size)