

Werkstückträger WT 2/H 19,05 mm für Transfersystem TS 2plus, ESD-geeignet - Bosch Rexroth 3842998755

Item no. BRR-3842998755 **Manufacturer** Bosch Rexroth

Manufacturer no. 3842998755

Aluminum workpiece pallet for the TS 2plus transfer system with a 19.05 mm plate thickness and a maximum permitted total weight of up to 240 kg. PE wear pads and integrated stop dampers ensure quiet, low-wear operation. Available fully assembled or as a self-assembly kit in 17 standard sizes from 400 x 400 mm to 1200 x 1200 mm.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Country of Manufacture	Germany
ESD-Ausführung	TEC
Weight	0.0099 kg
Zolltarifnummer	84662020



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The WT 2/H 19.05 workpiece pallet carries and transports workpieces within the TS 2plus transfer system - including operation with accumulation roller chain conveyors at a maximum permitted total weight of up to 240 kg (2 kg per cm of length). The 19.05 mm aluminum carrying plate provides the structural base; corner modules and sliders with PE wear pads minimize noise and wear. Integrated stop dampers absorb the impact when running onto preceding pallets, eliminating the need for separate damping accessories. Suitable for use in an EPA (electrostatic protected area).

- Maximum total weight up to 240 kg - handles heavy assemblies reliably
- PE wear pads for quiet operation and extended service life
- Integrated stop dampers - no additional damping accessories required
- ESD-suitable for use in electrostatic protected areas

- 17 standard sizes plus special dimensions on request
- Available fully assembled (MT = 1) or as a kit for self-assembly (MT = 0)

Technical data

Parameter	Value
Plate thickness dPL	19.05 mm
Carrying plate material	Aluminum
Corner module and slider material	PE (polyethylene)
ESD-suitable	Yes
Max. total weight mG	240 kg
Pallet width bWT	400 / 480 / 640 / 800 / 1040 / 1200 mm
Pallet length IWT	400 / 480 / 640 / 800 / 1040 / 1200 mm
Delivery state	Mounted (MT = 1) or kit, not mounted (MT = 0)
Scope of delivery	Carrying plate, corner modules, wear pads, damping elements
Recommended accessories	2x positioning bushing kit WT 2/H LE 2 (required when using a PE 2/H positioning unit)
Special dimensions	Available on request