

Umlenkeinheit UM 2/B für Transfersystem TS 2plus, ESD-geeignet - Bosch Rexroth 3842999090

Item no. BRR-3842999090

Manufacturer Bosch Rexroth

The Return UM 2/B redirects workpiece carriers at the end of a TS 2plus conveyor line, closing the belt circuit for continuous transport. The unit is ESD-suitable, fully assembled at the factory, and supplied with all fastening hardware for mounting on ST 2/... conveyor sections. Track widths from 160 to 1200 mm are available as preferred values, with custom widths on request.

TECHNICAL DATA

Ausführungsklasse **TEC**

Country of Manufacture **Germany**

Weight **0.1 kg**

Zolltarifnummer **84313900**


STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Return UM 2/B is a line component of the TS 2plus transfer system, providing belt direction reversal at the end of a conveyor section. Its ESD-suitable design makes it fit for transporting electrostatically sensitive assemblies and workpiece carriers in production and assembly environments.

- Track width 160 to 1200 mm - nine preferred values (160, 240, 320, 400, 480, 640, 800, 1040, 1200 mm) plus individual width variants available on request
- Conveyor medium length IUM 660 mm - fixed dimension for straightforward integration into existing TS 2plus lines
- ESD-suitable design for safe handling of electrostatically sensitive workpiece carriers and components
- Fully assembled on delivery - ready to install without on-site pre-assembly
- Includes all fastening material for direct mounting on ST 2/... conveyor sections

TECHNICAL DATA

boxic24.com

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@boxic24.com

boxic24.com

Page 1/2

Parameter	Value
Track width min (b min)	160 mm
Track width max (b max)	1200 mm
Preferred track width values	160, 240, 320, 400, 480, 640, 800, 1040, 1200 mm
Conveyor medium length (IUM)	660 mm
ESD-suitable	Yes
Delivery condition	Fully assembled
Scope of delivery	Incl. fastening material for ST 2/... conveyor sections
Individual width variants	Available on request