

EcoSlide Schiebewagen 30x30x160 mm, Aluminium eloxiert, Profilnut 8 - Bosch Rexroth 8981535477

Item no. BRR-8981535477 **Manufacturer** Bosch Rexroth

Manufacturer no. 8981535477

The EcoSlide trolley 30x30x160 runs on aluminum strut profiles with slot 8 at up to 12 m/min and handles compression loads up to 1500 N. A built-in spacer washer compensates tolerances between trolley and profile for smooth, low-play travel. Designed for 30 mm profile width with straightforward assembly.

TECHNICAL DATA



Article authenticity	Original product
Condition of article	New
Country of Manufacture	United States
Weight	0.489 kg
Zolltarifnummer	76169990

DESCRIPTION

The EcoSlide trolley 30x30x160 provides precise linear travel on aluminum framing profiles with slot 8 (30 mm profile width). The anodized aluminum body and included spacer washer deliver low-play movement and quick installation without special tooling.

- Compression load up to 1500 N and tensile load up to 750 N for demanding handling tasks
- Maximum torque around z-axis 200 Nm, around x-axis 20 Nm
- Sliding speed up to 12 m/min for dynamic applications
- Spacer washer included for tolerance compensation between trolley and profile
- Recommended accessories: N8 flat slider and flat lockable, clamping lever, screw, N8 sliding block

Technical data

Parameter	Value
Dimensions	30 x 30 x 160 mm
Profile slot	8

Parameter	Value
Profile width	30 mm
Material	Aluminum, anodized
Compression load Fmax	1500 N
Tensile load Fmax	750 N
Torque around x-axis Mmax	20 Nm
Torque around z-axis Mmax	200 Nm
Max. sliding speed	12 m/min
Weight	0.489 kg
Packaging unit	1

Machining note: To fit a clamping lever, the corresponding bore in the trolley must be drilled out to 9 mm.