

EcoSlide-Wagen 45x60x160 mm für Aluminiumprofil 60 mm - Bosch Rexroth 8981535479

Item no. BRR-8981535479 **Manufacturer** Bosch Rexroth

Manufacturer no. 8981535479

Linear sliding trolley in anodized aluminium for Bosch Rexroth profiles with 60 mm width and slot 10. Rated to 2500 N compression and 1250 N tensile load at up to 12 m/min sliding speed. A built-in spacer washer simplifies tolerance compensation between trolley and profile for fast assembly.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Country of Manufacture	United States
Weight	0.659 kg
Zolltarifnummer	76169990



DESCRIPTION

The EcoSlide trolley 8981535479 is a linear slide carriage in anodized aluminium, designed for Bosch Rexroth aluminium profiles with 60 mm width (profile slot 10). It is used in assembly and handling systems wherever components or tools must slide and be positioned along a profile rail.

- 2500 N compression and 1250 N tensile load capacity for demanding assembly tasks
- Maximum sliding speed of 12 m/min for smooth, efficient workflows
- Integrated spacer washer for straightforward tolerance compensation between trolley and profile
- Anodized aluminium construction: corrosion-resistant and lightweight at 0.659 kg
- Tool-free assembly; bore the clamping lever hole to 9 mm when using a clamping lever accessory

Technical data

Parameter	Value
Dimensions (L x W x H)	45 x 60 x 160 mm
Profile slot	10

Parameter	Value
Profile width	60 mm
Material	Aluminum, anodized
Compression load Fmax	2500 N
Tensile load Fmax	1250 N
Torque around x axis Mmax	80 Nm
Torque around z axis Mmax	200 Nm
Maximum sliding speed	12 m/min
Weight	0.659 kg
Packaging unit	1 piece
Recommended accessories	N10 flat slider, N10 flat lockable slider, spacer washer, clamping lever, N10 sliding block