

# Rad- und Rollenzubehör - Auer

## RBGSFV125x38P105x80

**Item no.** RBGSFV125x38P105x80 **Manufacturer** Auer

**Manufacturer no.** RBGSFV125x38P105x80

Wheel and castor accessory that turns Auer containers and large load carriers into rolling units without a forklift. Swivel casters with 360-degree rotation deliver high maneuverability.

### TECHNICAL DATA

|                        |                            |
|------------------------|----------------------------|
| Article authenticity   | <b>Original product</b>    |
| Condition of article   | <b>New</b>                 |
| Country of Manufacture | <b>Germany</b>             |
| Hinweis                | <b>Stück auf Palette -</b> |
| Weight                 | <b>0.1 kg</b>              |
| Zolltarifnummer        | <b>87168000</b>            |



### STANDARDS & COMPLIANCE

**ESD safe**

### DESCRIPTION

Wheel and castor accessory that turns Auer containers and large load carriers into rolling units without a forklift.

- Swivel casters with 360-degree rotation deliver high maneuverability.
- A total-lock version allows secure parking.
- Wheel sets ship matched to the container footprint with screws included and mount right away.
- Runner sets provide a fixed base for robust handling by forklift and pallet truck.

Used to retrofit and reconfigure containers, large load carriers and transport trolleys.

Wheels in rubber, plastic or conductive ESD rubber, brackets in galvanised steel or stainless steel. Manufactured in Germany.

## Technical data

|                       |                            |
|-----------------------|----------------------------|
| Description           | Rigid castor               |
| Wheel Ø x wheel width | 12.5 x 3.8 cm              |
| Bracket made of       | galvanised steel           |
| Fastening             | Mounting plate 105 x 80 mm |
| Design wheel          | Rubber wheel, black        |
| Total lock brake      | no                         |
| Thread guard          | yes                        |
| Weight                | 863 g                      |
| Load capacity         | 100 kg                     |
| Bearing               | Sliding bearings           |
| Note                  | without mounting material  |