

Nutenstein 10, M5/M8, einschwenkbar, Stahl verzinkt - Bosch Rexroth 3842557262

Item no. BRR-3842557262

Manufacturer Bosch Rexroth

Swivel-in T-slot nut for profile slot 10, made from galvanized steel with dual thread sizes M5 and M8. Length 30 mm, groove retention up to 18,000 N. Installs at any point along the profile without access to the end.

TECHNICAL DATA

Country of Manufacture	China
Weight	0.136 kg
Zolltarifnummer	73181900



DESCRIPTION

The 3842557262 is a swivel-in sliding block for Bosch Rexroth aluminum profiles with slot size 10. Manufactured from galvanized steel, it combines M5 and M8 thread sizes in a single component, allowing insertion at any position along the profile slot without needing a free profile end.

- **Dual thread sizes:** M5 and M8 in one part, reducing stock requirements and simplifying assembly planning.
- **Swivel-in design:** Insert at any point along the profile - no disassembly or end access required.
- **High retention force:** Min. groove retention 8,000 N, max. 18,000 N - reliable under mechanical load in machine building applications.
- **Galvanized steel construction:** Corrosion resistance for industrial environments; length 30 mm, dimension b 14 mm, h 5.3 mm.
- **Packaging unit of 100:** Cost-efficient for series production and large-scale frame assembly.

TECHNICAL DATA

Attribute	Value
Profile slot	10
Thread size	M5; M8
Swivel-in	Yes
Length l	30 mm

Attribute	Value
Dimension b	14 mm
Dimension h	5.3 mm
Dimension h1	1.5 mm
Min. groove retention (Fmin)	8,000 N
Max. groove retention (Fmax)	18,000 N
Material	Steel, galvanized
Weight	0.136 kg
Packaging unit	100 pcs