

M12 Sensor-/Aktorbox 4-fach, 10 m PUR-Festkabel, A-kodiert, 24V DC - LED2WORK 200300-01


Item no. L2W-200300-01 **Manufacturer** LED2WORK

Manufacturer no. 200300-01

Passive M12 distribution box with 4 ports and a 10 m PUR fixed cable, connects up to four 24V DC LED2WORK luminaires to a controller or power supply. A-coded, IP67, UL listed.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Country of Manufacture	Germany
ESD-Ausführung	TEC
Weight	0.5 kg
Zolltarifnummer	85366990



STANDARDS & COMPLIANCE

ESD safe IEC 61076-2-101

DESCRIPTION

The M12 sensor/actuator box connects up to four 24V DC LED2WORK luminaires to a controller or power supply. The passive box has four A-coded M12 ports and is connected via a 10 m PUR fixed cable.

Benefits

- Four M12 ports for up to four 24V DC luminaires on one supply
- Fixed 10 m PUR cable, no extra field wiring required
- 2000 mA load per pin, gold-plated CuSn contacts
- IP65/IP67 protection, RoHS compliant and UL listed, mechanical life >100 mating cycles

Technical data

- **Model:** connection accessory
- **Design:** M12-A distribution box, 4-port, with fixed cable
- **Coding:** A-coded, 4-pole
- **Suitable for:** LED2WORK luminaires 24V DC, except RGB and RGB-W
- **Cable length:** 10 m
- **Load per pin:** 2000 mA
- **Protection rating (mounted):** IP65, IP67
- **Operating temperature:** -30 °C to +90 °C
- **Material:** PA contact carrier, FPM/FKM seal, gold-plated CuSn contacts, PUR cable
- **Standards:** IEC 61076-2-101
- **Dimensions:** 115.4 mm x 54 mm x 25.5 mm
- **Weight:** 500 g
- **Certifications:** CE, RoHS, UL
- **Mechanical life:** >100 mating cycles
- **Made in:** Germany

Applications

For the central connection of several 24V DC machine or signal lights in machines and plants, for example a shared supply via a controller. Not for RGB and RGB-W luminaires.