

Schaltnetzteil 24V DC 60 W, IP67, M12 Buchse/offene Enden - LED2WORK 210100-06

Item no. L2W-210100-06 **Manufacturer** LED2WORK

Manufacturer no. 210100-06

Rugged AC/DC industrial power supply with a fixed 24V DC output and 60 W, in a sealed die-cast aluminium housing. Enough power for several daisy-chained LED2WORK luminaires, connected via M12 A-coded.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Country of Manufacture	China
ESD-Ausführung	TEC
Weight	1.1 kg
Zolltarifnummer	85044095



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The LED2WORK industrial power supply delivers a fixed 24V DC output of up to 60 W, enough to power several luminaires connected in series (daisy-chaining). The sealed die-cast aluminium housing with internal thermally conductive silicone is built for rugged continuous operation.

Key benefits

- Fixed 24V DC output at 60 W, sufficient for several daisy-chained LED2WORK luminaires
- High IP67 protection rating for use in demanding environments
- Sealed die-cast aluminium housing with internal thermally conductive silicone
- 110-240 V AC input via open 3-core cable, output via M12 A-coded
- Cable fully protected by a flexible metal conduit
- Active PFC, broad approval base

Technical data

- **Model:** constant-voltage power supply
- **Design:** IP67, metal housing, input open ends, output M12 socket, cable protection flexible metal conduit
- **Output voltage:** 24V DC
- **Output power:** 60 W
- **Connection:** M12 socket, A-coded
- **Protection rating:** IP67
- **Dimensions:** 171 mm x 61.5 mm x 36.8 mm
- **Weight:** 1100 g
- **Certifications:** active PFC, IP65, IP67, ICC, CB, CE, UKCA, UL8750 Type HL

Applications

For rugged power supply of LED2WORK 24V DC luminaires in machines and plants, including daisy-chaining of several luminaires in damp or harsh environments.