

Strebenprofil 15x22,5 mm, 1 Nut, Aluminium eloxiert, 1000 mm - Bosch Rexroth 3842992475-1000

Item no. BRR-3842992475-1000

Manufacturer Bosch Rexroth

Compact aluminum strut profile with a 15x22.5 mm cross-section, one open slot (10 mm width), and a 45 mm modular dimension for integration into Bosch Rexroth assembly systems. Anodized natural finish, available cut-to-length from 80 to 3000 mm. Recommended accessories: cover caps 15x22.5 in signal gray or black.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
Hinweis	Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.
Weight	0.0099 kg
Zolltarifnummer	76169990



DESCRIPTION

The strut profile 15x22.5 (article 3842992475) is a slender aluminum construction profile from the Bosch Rexroth assembly system. Its 15x22.5 mm cross-section, single open slot (10 mm width), and 45 mm modular dimension make it a direct fit for existing Rexroth profile structures - suitable as a strut, cross-connector, or frame element in assembly fixtures, guards, and industrial frames.

- Anodized aluminum (natural) - lightweight and corrosion-resistant
- 15x22.5 mm cross-section - space-saving for slender support structures and bracing
- One open profile slot (10 mm) - compatible with the Rexroth slot system for connectors and fasteners
- Cut-to-length: minimum 80 mm, maximum 3000 mm, packaging unit 1 piece
- Profile surface 1.3 cm², area moment of inertia I_x 0.8 cm⁴ / I_y 0.3 cm⁴

TECHNICAL DATA

Property	Value
Cross-section	15x22.5 mm
Profile slot (width)	10 mm
Open slots	1
Modular dimension	45 mm
Profile type	Standard

boxic24.com

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@boxic24.com

boxic24.com

Page 1/2

Property	Value
Color	Natural (anodized)
Material	Aluminum, anodized
Length min (L min)	80 mm
Length max (L max)	3000 mm
Profile surface (A)	1.3 cm ²
Area moment of inertia X (I _x)	0.8 cm ⁴
Area moment of inertia Y (I _y)	0.3 cm ⁴
Moment of resistance X (W _x)	0.9 cm ³
Moment of resistance Y (W _y)	0.6 cm ³
Mass (m)	0.3 kg/m
Packaging unit	1 piece
Recommended accessories	Cover cap 15x22.5 signal gray, Cover cap 15x22.5 black