

Strebenprofil 40x160L M12/M12, 1000 mm - Bosch Rexroth 3842993145-1000

Item no. BRR-3842993145-1000

Manufacturer Bosch Rexroth

Heavy-section strut profile with 40x160L cross-section and M12 threads in all central bores, designed for load-bearing frame structures in the Bosch Rexroth aluminum profile system. The anodized aluminum extrusion offers 10 open slots, ESD suitability, and an area moment of inertia of 466.7 cm⁴ in the x-direction. Supplied at 1000 mm; custom lengths from 110 to 6000 mm available on request.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
Hinweis	Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.
Weight	0.0099 kg
Zolltarifnummer	76169990



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Strut Profile 40x160L M12/M12 is a structural section of the Bosch Rexroth aluminum profile system with a 40x160 mm cross-section and a modular dimension of 40 mm. M12 threads in all central bores and D17 clearance holes in slots B/J, C/I, D/H, and E/G make it immediately ready for connection with standard Rexroth connectors. The anodized aluminum finish meets ESD requirements, making the profile suitable for electrostatically sensitive production and assembly environments.

- 10 open slots (profile slot 10) for flexible fastening and attachment options along the full length
- High bending stiffness: area moment of inertia $I_x = 466.7 \text{ cm}^4$, moment of resistance $W_x = 58.3 \text{ cm}^3$
- ESD-suitable - safe for use in electrostatically sensitive environments
- Anodized aluminum, natural color - corrosion-resistant and durable
- Flexible cut-to-length: 1000 mm stock length; special lengths 110 to 6000 mm on request

TECHNICAL DATA

Property	Value
Cross-section	40x160 mm
Profile type	Standard
Modular dimension	40 mm
Profile slot	10
Open slots	10
Length (this version)	1000 mm
Length min / max	110 mm / 6000 mm
Profile adaption	M12 in all central bores; D17 in slots B/J, C/I, D/H, E/G
Material	Aluminum, anodized
Color	Natural
ESD	Yes
Mass [m]	5.5 kg
Profile surface [A]	20.5 cm ²
Area moment of inertia I _x	466.7 cm ⁴
Moment of resistance W _x	58.3 cm ³
Area moment of inertia I _y	37.2 cm ⁴
Moment of resistance W _y	18.6 cm ³
Torsional moment of inertia I _t	25.8 cm ⁴
Moment of torsion resistance W _t	14.6 cm ³
Packaging unit	1
Recommended accessories	Cover cap 40x80, signal gray; Cover cap 40x80, black