

Strebenprofil 11x20, Aluminium eloxiert, 1-Nut, L=1000 mm - Bosch Rexroth 3842993688-1000

Item no. BRR-3842993688-1000

Manufacturer Bosch Rexroth

Compact aluminium strut profile with an 11x20 mm cross-section and one size-8 profile slot for lightweight structural connections and bracing within the 30 mm modular grid. Supplied anodized in natural colour at 1000 mm; standard profile finishing D7.8 / D11 available, minimum length applies. Recommended accessories: cover caps 11x20 in black or signal gray.

TECHNICAL DATA

Ausführungsklasse	TEC
Country of Manufacture	Germany
Hinweis	Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.
Weight	0.0099 kg
Zolltarifnummer	76042100



DESCRIPTION

The Bosch Rexroth Strut Profile 11x20 is a slim aluminium profile designed for bracing, diagonal members, and lightweight framing within the MK profile system. Its 11x20 mm cross-section and single size-8 open slot integrate directly with standard T-slot hardware on the 30 mm modular grid.

- 11x20 mm cross-section - minimal footprint for space-critical diagonal and strut applications
- Anodized aluminium, natural colour - corrosion-resistant surface protection, ready to install
- Size-8 open profile slot - compatible with standard slot nuts and connectors on the 30 mm grid
- Standard profile finishing D7.8 / D11 - available from the factory; observe minimum length requirements
- Cut-to-length from 50 mm to 2000 mm - this article covers the 1000 mm cut length
- Recommended accessories: cover cap 11x20 in black or signal gray

TECHNICAL DATA

Property	Value
Cross-section	11x20 mm
Profile type	Standard
Profile slot	8
Open slots	1
Modular dimension	30 mm

Property	Value
Length (this article)	1000 mm
Length min / max	50 mm / 2000 mm
Material	Aluminium, anodized
Colour	Natural
Mass	0.3 kg/m
Profile surface (A)	1 cm ²
Area moment of inertia I _x	0.5 cm ⁴
Area moment of inertia I _y	0.1 cm ⁴
Moment of resistance W _x	0.7 cm ³
Moment of resistance W _y	0.3 cm ³
Standard profile finishing	D7.8 / D11
Packaging unit	1 piece