

TUBELED_40 II Leuchtenhalter 110° Magnetwinkel aus Edelstahl, 600 N, 1 Paar - LED2WORK 210200-12

Item no. L2W-210200-12 **Manufacturer** LED2WORK

Manufacturer no. 210200-12

Stainless steel magnetic brackets supplied as a pair for non-destructive mounting of the TUBELED_40 II. With 600 N holding force they attach to any magnetic surface, and the light tilts through 110° and locks in place.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Country of Manufacture	Germany
ESD-Ausführung	TEC
Weight	0.1 kg
Zolltarifnummer	94059900



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The stainless steel TUBELED_40 II magnetic bracket allows non-destructive mounting: the two brackets are fixed through the threaded holes in the fixture end caps and then attach with 600 N holding force to any magnetic surface. The light can be tilted through 110° and locked in position.

Key benefits

- Non-destructive magnetic mounting without drilling
- Holding force of 600 N on any magnetic surface
- Tilt adjustment through 110° with locking
- Corrosion-resistant stainless steel with hard-magnetic alloy, supplied as a pair

Technical data

- **Model:** light bracket TUBELED_40 II
- **Type:** angle bracket
- **Quantity:** 1 pair
- **Magnet holding force:** 600 N
- **Material:** stainless steel, magnet of hard-magnetic alloy
- **Dimensions:** 40 mm x 28 mm x 38 mm
- **Weight:** 100 g
- **Adjustment range:** 110° tilt and lock

Applications

Suitable for the surface-mounted lights TUBELED_40, TUBELED_40 II, TUBELED_40 II RGB-W and TUBELED_40 Element. For fast, drill-free mounting of machine lighting on magnetic surfaces.