

Gehrungswinkel für Nut 10, Stahl verzinkt - Bosch Rexroth 3842563228

Item no. BRR-3842563228 **Manufacturer** Bosch Rexroth**Manufacturer no.** 3842563228

Miter bracket for right-angled, miter-cut connections between Rexroth slot 10 aluminum profiles. No profile finishing required with open slots; closed slots need only a through-hole for screwdriver access. Includes 4 headless setscrews ISO 913 M10x10; ESD-suitable, galvanized steel.

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
Country of Manufacture	Germany
Weight	0.045 kg
Zolltarifnummer	83024900



STANDARDS & COMPLIANCE

ESD safe ISO 913

DESCRIPTION

The miter bracket for slot 10 creates right-angled miter connections between Rexroth aluminum construction profiles. Open profile slots require no finishing work; closed profile slots need only a through-hole for screwdriver access. Fastening hardware - 4 headless setscrews ISO 913 M10x10 - is included, so the connection is ready to assemble straight from the box.

- Right-angled miter connection with no profile finishing on open slots
- ESD-suitable for use in electrostatically protected assembly areas
- Complete with fastening material - no additional hardware required
- Packaging unit: 20 pieces

Technical data

Specification	Value
Profile slot	10
Material	Steel, galvanized

Specification	Value
Fastening material	4x headless setscrew ISO 913 M10x10, steel, galvanized
Scope of delivery	Incl. fastening material
ESD	Yes
Weight	0.045 kg
Packaging unit	20 pieces