

Strebenprofil 15x22,5 mm, L=3000 mm, Aluminium eloxiert, ESD-geeignet - Bosch Rexroth 3842563232

Item no. BRR-3842563232

Manufacturer Bosch Rexroth

Compact aluminum strut profile with a 15x22.5 mm cross-section and 3000 mm length for use in assembly and workstation structures on the 45 mm grid. Anodized finish, ESD-suitable, one open slot (profile slot 10) for versatile connection options.

TECHNICAL DATA

Country of Manufacture **Germany**

Hinweis
Gemäß der aktuellen Preisstruktur werden für Bestellungen von Profilen mit einer Länge von 1500 mm zusätzliche Kosten in Höhe von 80,00 Euro berechnet.

Length **3000 mm**

Weight **1.023 kg**

Zolltarifnummer **76042100**


31447

STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The strut profile 15x22.5 (article 3842563232) is a slender aluminum structural profile based on the 45 mm modular grid. It is designed for lightweight bracing, cover frames, and auxiliary structures within the Bosch Rexroth aluminum profile system - well suited for space-constrained applications where ESD protection is required.

- Anodized aluminum: corrosion-resistant, natural color, ESD-suitable
- One open slot (profile slot 10) accepts connectors, brackets, and fastening elements
- 45 mm modular dimension: fully compatible with the Bosch Rexroth aluminum profile system
- Supplied as a single rod in standard length, packaging unit 1 piece
- Recommended accessories: cover cap 15x22.5, signal gray or black

TECHNICAL DATA

Property	Value
Cross-section	15x22.5 mm
Length [L]	3000 mm
Modular dimension	45 mm

boxic24.com

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@boxic24.com

boxic24.com

Page 1/2

Property	Value
Profile slot	10
Open slots	1
Profile type	Standard
Profile surface [A]	1.3 cm ²
Area moment of inertia x-direction [Ix]	0.8 cm ⁴
Moment of resistance x-direction [Wx]	0.9 cm ³
Area moment of inertia y-direction [Iy]	0.3 cm ⁴
Moment of resistance y-direction [Wy]	0.6 cm ³
Mass [m]	0.3 kg/m
Weight (rod)	1.023 kg
Material	Aluminum, anodized
Color	Natural
ESD	Yes
Condition on delivery	Single rod in standard length
Packaging unit	1 piece