

Lenkrolle mit Feststeller 160 x 40 mm TPE-Bereifung, elektrisch leitfähig - Fetra 71463

Item no. FE-71463

Manufacturer Fetra

EAN 4017976714639

Swivel castor with electrically conductive TPE tyre and 160 x 40 mm wheel size rated for 200 kg. The castor swivels through 360° for agile manoeuvring in tight spaces. The total-stop brake locks the wheel and swivel head at the same time and secures the equipment reliably against rolling away.

TECHNICAL DATA

Ausführungsklasse **ESD (antistatic)**Country of Manufacture **China**Warranty **10 years**Weight **3 kg**Zolltarifnummer **73269098**

STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The Fetra swivel castor 71463 with brake is a replacement and retrofit castor with electrically conductive TPE tyre and 160 x 40 mm wheel size. It carries up to 200 kg and is built as a durable component for transport equipment, trolleys and machinery in continuous duty.

BENEFITS

- Load capacity up to 200 kg per castor
- The electrically conductive TPE tread drains electrostatic charges in a controlled way through the wheel to the floor, which makes it suitable for ESD protected areas to IEC 61340-5-1. The tread runs easily, quietly and leaves no marks.
- The castor swivels through 360° for agile manoeuvring in tight spaces.
- Total-stop brake locks wheel and swivel head simultaneously

TECHNICAL DATA

- Load capacity: 200 kg
- Wheel size: 160 mm
- Wheel width: 40 mm

- Tyre: electrically conductive TPE tyre
- Mounting plate: 135 mm
- Bolt hole spacing: 105 mm
- Bolt hole diameter: 11 mm
- Type: Swivel castor with brake

USE

A spare part for Fetra transport equipment and a retrofit for trolleys, racks and machines. The mounting plate allows quick fitting to an existing frame.

QUALITY

Fetra quality with a 10-year guarantee.