

Transport dolly Maxi HD with linking system 82 x 62 cm, polyamide wheels with brake - Auer RO V 86.4 HD PA FE.L-5015

Item no. RO V 86.4 HD PA FE.L-5015**Manufacturer Auer**

Transport dolly measuring 82 x 62 cm for Euro containers with an 80 x 60 cm footprint. Four polyamide swivel castors, two of them with a brake, secure the dolly against rolling away when parked. The linking system couples several dollies into a train.

TECHNICAL DATA

Weight **7.13 kg**



DESCRIPTION

The Maxi HD transport dolly moves Euro containers with an 80 x 60 cm footprint close to the floor. Its 250 kg load rating carries fully loaded and stacked containers.

BENEFITS

- Four swivel castors allow tight manoeuvring, two of them with a brake secure the loaded dolly when parked.
- Polyamide wheels with a 12.5 cm diameter roll smoothly and resist oil, grease and many chemicals.
- Linking system couples several dollies into a continuous transport train.
- ABS frame with a 250 kg load rating at a dead weight of 7.13 kg.

TECHNICAL DATA

- External dimensions L x W: 82 x 62 cm
- Wheel configuration: 2 swivel castors, 2 swivel castors with brake
- Frame material: ABS
- Wheel material: PA (polyamide)
- Wheel diameter: 12.5 cm
- Load rating: 250 kg
- Weight: 7.13 kg

- Colour: sky blue similar to RAL 5015

APPLICATIONS

Suited to order picking, internal transport and staging at workstations where the dolly must stay put. The brake prevents unwanted rolling on ramps and at packing stations.