

Waldmann Aufbauleuchte MACH LED PLUS.seventy - MQAL 36 N, L: 510 mm, Power

Item no. WL35432

Manufacturer Waldmann

Surface mounted light MACH LED PLUS.seventy - MQAL 36 N, L:
510 mm, Power

TECHNICAL DATA

Weight

0.1 kg



DESCRIPTION

Maintenance-free LED technology. Power version. Very low-glare, homogeneous light with soft transitions. Outer diameter 70 mm for the replacement of classic tubular lights. Robust aluminium housing with solid safety glass cover. Side parts made of high performance plastic. Sealed M12 connector. Viton seal for a high degree of protection. Chemically resistant to many media such as oils or cooling lubricants. Insensitive to shocks and vibrations. Ideal for high mechanical and thermal loads. Connection to mains voltage.

- Control gear: Electronic ballast
- Connected loads: 100/120/220-240 V, 50/60 Hz
- Luminous flux: approx. 1650 lm
- luminous efficacy: approx. 78 lm/W
- Light distribution: direct
- Light colour: neutral white
- Colour rendering (Ra): >80
- Technology: switchable
- Operation: external
- Lamp cover: Lens shade, clear (colourless)
- Mains connection: Connector, Series 814
- Type: Surface-mounted version
- Mounting: L-angle (accessory), clamp (accessory)

- Length: 510 mm
- Special feature: Power assembly
- Em: 591 lx, Emax: 768 lx, Emin: 382 lx

PRODUCT DETAILS

item number	WL35432
model	MQAL 36 N
manufacturer	WALDMANN
manufacturer item number	113059000-00580606
length	845 mm
width	90 mm
depth	80 mm
order unit	piece
luminous flux	1650 lm
Lamp or magnifier type	Surface mounted light
connections	100/120/220-240 V, 50/60 Hz
colour temperature	5000 °K
power	21 W
equipping	LED, energy efficiency class A+
housing colour	Aluminium, anodised, aluminium coloured (colourless anodised)
protection class	1
protection class	67 IP
ESD safe	no