

Waldmann Aufbauleuchte MACH LED PLUS.seventy - MQAL 30 S, L: 790 mm, Eco

Item no. WL35449

Manufacturer Waldmann

Surface mounted light MACH LED PLUS.seventy - MQAL 30 S, L:
790 mm, Eco

TECHNICAL DATA

Weight **0.1 kg**



DESCRIPTION

Maintenance-free LED technology. Eco version. Very low-glare, homogeneous light with soft transitions. Outer diameter 70 mm for the replacement of classic tubular lights. Robust aluminium housing with solid safety glass cover. Side parts made of high performance plastic. Sealed M12 connector. Viton seal for a high degree of protection. Chemically resistant to many media such as oils or cooling lubricants. Insensitive to shocks and vibrations. Ideal for high mechanical and thermal loads. Connection to machine voltage.

- without control gear
- Connected loads: 18-30 V; DC
- Luminous flux: approx. 1250 lm
- luminous efficacy: approx. 96 lm/W
- Light distribution: direct
- Light colour: neutral white
- Colour rendering (Ra): >80
- Technology: switchable
- Operation: external
- Lamp cover: Lens shade, clear (colourless)
- Mains connection: 763 series connectors
- Type: Mounting version
- Mounting: L-angle (accessory), clamp (accessory)

- Length: 790 mm
- Special feature: Eco-assembly
- Em: 444 lx, Emax: 573 lx, Emin: 283 lx (measuring distance: 100 cm)

PRODUCT DETAILS

item number	WL35449
model	MQAL 30 S
manufacturer	WALDMANN
manufacturer item number	113077000-00580663
length	1020 mm
width	90 mm
depth	80 mm
order unit	piece
luminous flux	1250 lm
Lamp or magnifier type	Surface mounted light
connections	18-30 V; DC
colour temperature	5000 °K
power	13 W
equipping	LED, energy efficiency class A+
housing colour	Aluminium, anodised, aluminium coloured (colourless anodised)
protection class	3
protection class	67 IP
ESD safe	no