

## Waldmann Gestängeleuchte ROCIA.focus, RFD 600/850/DS - 10° Spot

Item no. WL42292

Manufacturer Waldmann

pole lamp ROCIA.focus, RFD 600/850/DS - 10° spotlight

### TECHNICAL DATA

Weight

**0.1 kg**

### DESCRIPTION

Maintenance-free LED technology. Powerful high power LEDs for maximum light. With narrow beam light characteristic. Continuous and flicker-free dimming (switchable). Robust aluminium housing with solid safety glass cover. Viton seal for a high degree of protection. Chemically resistant to many media such as oils or cooling lubricants. Precisely adjustable boom. Connection to machine voltage.

- without control gear
- Connected loads 12-28 V; AC and 12-40V; DC
- Luminous flux: approx. 600 lm
- luminous efficacy: approx. 75 lm/W
- Light distribution: direct, narrow beam
- Colour rendering (Ra): >80
- Glare control: Optics
- Technology: switchable, infinitely dimmable
- Operation: Pushbutton
- Lamp cover: Glass screen
- Joint relief: Spring
- Power supply cable: approx. 3 m; with free stranded wire/cable ends
- Mounting: Screw-on flange; base, table clamp (accessories), wall bracket (accessories)
- Special features: Spot with 10° beam angle
- Em: 5088 lx, Emax: 30053 lx, Emin: 682 lx (measuring distance 50 cm)

## PRODUCT DETAILS

|                          |                                         |
|--------------------------|-----------------------------------------|
| item number              | WL42292                                 |
| model                    | ROCIA.focus RFD600/850/D                |
| manufacturer             | WALDMANN                                |
| manufacturer item number | 113182000-00680110                      |
| length                   | 710 mm                                  |
| width                    | 300 mm                                  |
| depth                    | 105 mm                                  |
| order unit               | piece                                   |
| Lamp or magnifier type   | rod light                               |
| luminous flux            | 600 lm                                  |
| connections              | 12-28 V; AC and 12-40 V; DC             |
| dimnable                 | yes                                     |
| colour temperature       | 5000 °K                                 |
| power                    | 8 W                                     |
| equipping                | LED Energy efficiency class A+          |
| attachment               | Pedestal, Table mounting, Wall mounting |
| housing colour           | Aluminium, anodised, black              |
| protection class         | 3                                       |
| protection class         | 67 IP                                   |
| ESD safe                 | no                                      |