

Waldmann Aufbauleuchte Mach Plus.fourty-MLAL 27 S, L: 365 mm, 10,5 W

Item no. WL48318

Manufacturer Waldmann

Surface-mounted light Mach Plus.fourty-MLAL 27 S, L: 365 mm,
10.5 W

TECHNICAL DATA

Weight **0.1 kg**



DESCRIPTION

The MACH LED Plus 40 machine light from Waldmann supports multiple visual tasks, even where space is limited. With an outer diameter of 40 mm and a minimum length of 190 mm, the MACH LED PLUS 40 provides high luminosity with an impressive output luminance. This workstation luminaire is state-of-the-art with the latest LEDs, developed optics and a modern housing concept. With a protection class of IP67, the MACH LED PLUS 40 is water and oil-tight and resistant to cooling lubricants.

- LED technology
- Colour temperature neutral white 5 000 K
- Colour rendering Ra > 80
- Beam angle 40° (optics) or 90° (reflector)
- Colourless anodised aluminium housing, black side panels made of high-performance plastic, 4 mm thick safety glass
- Mounting by means of various holders from the accessories
- Maximum permissible ambient temperature Tamax 50 °C
- LED service life (L70) > 60 000 h
- Vibration resistant at 10 to 55 Hz (amplitude 0.35 mm) Shock resistant up to 50 g
- Protection class IP67; protection class III
- Connection via M12 plug connection, A-coded

PRODUCT DETAILS

item number	WL48318
manufacturer	WALDMANN
manufacturer item number	113162000-00662685
length	390 mm
order unit	piece
material	aluminium, plastic
Lamp or magnifier type	Surface mounted light
connections	20-28 V dc
dimmable	no
colour temperature	50000 °K
power	10.5 W
equipping	LED
housing colour	Colorless anodized aluminum housing
protection class	3
protection class	67 IP
ESD safe	no